

LANYARD "V"



Lanyard "V" / W2200*

Lanyard

- tested according to EN 354 standard for lanyards
- used for working at height, especially for self-protection when moving from one place to another
- on both ends of the rope stitched loops with reinforcement for placing carabiners are made
- middle loop is attached to the harness with carabiners and an energy-absorbing device
- seam is protected by a transparent plastic cover which also allows its easy inspection
- lanyards have different color of the eyes according to their length

Code	length	length	eye color	strength	weight
W2200W001	25/45 cm	10/17 in	yellow	22 kN	130 g • 4.6 oz
W2200W002	25/65 cm	10/30 in	blue	22 kN	145 g • 5.1 oz
W2200W100	100/100 cm	40/40 in	red	22 kN	225 g • 7.9 oz

- also available in black

Code	length	length
W2200B001	25/45 cm	10/17 in
W2200B002	25/65 cm	10/30 in
W2200B100	100/100 cm	40/40 in

Color	white + yellow, blue or red eyes; also available in black
Weight	130, 145, 225 g • 4.6, 5.1, 7.9 oz
Strength	22 kN
Length	25/45, 25/65, 100/100 cm • 10/17, 10/30, 40/40 in
Diameter	10.5 mm
Length deviation	25/45, 25/65 cm -2/+3 cm; 100/100 cm -3/+5 cm

CE 1019 EN 354

Related goods